



SOLAR 1.5KVA 24V MPPT INVERTER



HIGH CURRENT CHARGER



DSP BASED TECHNOLOGY



NOISELESS OPERATION



PURE SINE WAVE OUTPUT

CONTACT US


✉ sales@beaconpowersys.com

🌐 www.beaconpowersys.com

☎ PH: 85939 60000,
Toll Free: 1800 121 3511

SOLAR BE 1.5 KVA 24 V MPPT INVERTER

TECHNICAL DATA SHEET



SYSTEM DETAILS

System Model Name	BE 015024
Capacity	1500VA/1200W
Nominal DC Voltage	24V
Inv. Switching Device	MOSFET
Grid Charger Topology	Inv. Bridge Boost
Solar Switching Device	MOSFET
Solar Charger Topology	MPPT Buck

MECHANICAL DATA

Dimension (L X W X H)	295mm X 240mm X315mm
Operating Temperature	0-50°C
Cooling	FORCED AIR COOLING
Noise@1m	<50dB
Weight(kg)	16kg
Max Relative Humidity@ 25°C	95%

PARAMETERS(GRID)

Nominal Grid Voltage	230 VA 1φ
Nominal Frequency	50Hz ±.1%
UPS mode	190-255V
Battery Charging Voltage	28.8 V
Retrigger at	27 V

PARAMETERS(SOLAR)

VOC max	80-100V DC
Max Panel	900Wp
Battery Charging Current Control (Optional)	>800Wp(BM)
Battery Charging Voltage	29 V DC

MODE SETTING

Grid to Battery	28.8 V DC
Grid Reconnect	23 V DC

Switches & Controls

System	System ON/OFF
Mode Select	UPS/ Inverter
Charger Select	Grid/ Solar



PARAMETERS(INVERTER)

Nominal Output Voltage	220VAC 1 ϕ
Nominal Frequency	50Hz
Output Waveform	Pure Sine Wave
Battery Low Buzzer	22.4 V
Battery Low Cut	21.6 V

PROTECTIONS

Over Load, Short Circuit, Over Temperature

LCD

SINGLE LINE DISPLAY	AC Input Voltage, AC Output Voltage, Charging Mode Grid/Solar, Grid Charging Current, Temperature, Output Load
Fault Conditions	Battery Low, OverLoad, No Feedback, Over Temperature

DISPLAY

